

## CLAIMS

1. An N-way set-associative cache memory comprising:
  - a control register operable to indicate one or more ways among N ways;
  - 5 a control unit operable to activate the way indicated by said control register; and
  - an updating unit operable to update contents of said control register.
- 10 2. The cache memory according to Claim 1,
  - wherein said control unit is operable to restrict at least replacement, for a way other than the active way indicated by said control register.
- 15 3. The cache memory according to Claim 1, further comprising:
  - a tag holding unit, provided for each of the ways, operable to hold, as a tag, a cache data address; and
  - N-comparison units operable to judge whether a hit or a mishit has occurred, by comparing a tag address and N-tags
  - 20 outputted by said tag holding unit, the tag address being an upper portion of a memory access address outputted from a processor,
  - wherein said control unit is operable to disable a comparison unit corresponding to a way other than the active way indicated by said control register.
- 25 4. The cache memory according to Claim 3,
  - wherein said control unit is operable to disable tag outputting to a comparison unit, for a cache address holding unit corresponding to the way other than the active way indicated by said control
  - 30 register.
5. The cache memory according to Claim 3,

wherein, when a memory access address is outputted from the processor, said control unit is operable to:

control said comparison units to perform, for a maximum of two times, tag comparison for the memory access address;

5       disable, in a first tag comparison, a comparison unit corresponding to the way other than the active way indicated by said control register; and

cause said comparison units to perform a second comparison, without disabling the comparison unit corresponding to the way  
10   other than the active way, in the case where it is judged that a mishit has occurred in the first tag comparison.

6.     The cache memory according to Claim 5,  
       wherein said control unit is operable to disable, in the second  
15   tag comparison, the comparison unit corresponding to the way other than the active way.

7.     The cache memory according to Claim 2,  
       wherein said control unit is operable to prohibit status  
20   updating for the way other than the active way indicated by said control register.

8.     The cache memory according to Claim 2,  
       wherein said control unit is operable to prohibit updating of  
25   information indicating an access order of the way other than the active way indicated by said control register.

9.     The cache memory according to Claim 2, further comprising  
       a reset unit operable to reset the information indicating an  
30   access order for the ways, when the contents of said control register are updated by said updating unit.

10. The cache memory according to Claim 9,  
wherein the information indicating the access order is 1-bit  
data for each cache entry,

said cache memory further comprises

5 a register operable to hold data indicating a round position for  
selecting, in a round robin, one way from a plurality of replaceable  
ways, and

said reset unit is operable to reset said register when the  
contents of said control register are updated by said updating unit.

10

11. The cache memory according to Claim 2,  
wherein said updating unit includes:

a holding unit operable to hold way data for respective tasks,  
which specifies a way to be activated; and

15

a rewriting unit operable to rewrite said control register so as  
to hold way data corresponding to a task being executed.

12. The cache memory according to Claim 11,

20 wherein said holding unit is operable to hold the way data as  
part of context data for the respective tasks which is stored in a  
memory, and

during task switching, said rewriting unit is operable to save,  
in the memory, way data of a current task, inside said register, and  
to restore, from the memory to said control register, way data of a  
25 next task.

13. The cache memory according to Claim 12,

wherein said holding unit is operable to hold the way data for  
the respective tasks, and

30

said rewriting unit includes:

an address storage unit operable to store an address range of  
the respective tasks, stored in the memory;

an identification unit operable to identify the task being executed, based on the address range stored in the address storage unit and an instruction fetch address outputted from a processor; and

5           a selection unit operable to select, from said holding unit, way data corresponding to the identified task being executed.

14.   The cache memory according to Claim 12,  
          wherein said holding unit is operable to hold the way data for  
10   the respective tasks,

          said rewriting unit includes:

          a selection unit operable to select way data from said holding, according to a task number outputted from a processor unit, the way data corresponding to a task being executed; and

15           a writing unit operable to write the selected way data into said control register.

15.   The cache memory according to Claim 11,  
          wherein way data held in said holding unit is assigned to a  
20   task, by an operating system.

16.   The cache memory according to Claim 1,  
          wherein a unit of replacement for respective ways can be switched between a line size of a cache entry and a size which is one  
25   over two to the nth power of the line size,

          said control register is further operable to indicate a replacement size for respective tasks, and

          said control unit is operable to perform replacement control with the replacement size indicated by said control unit.

30

17.   The cache memory according to Claim 16,  
          wherein said control unit is operable to restrict at least

replacement for a way other than the active way indicated by said control register, and to perform replacement on the active way indicated by said register, with the size indicated by said control register.

5

18. The cache memory according to Claim 17,  
wherein said updating unit includes:

a holding unit operable to hold way data for respective tasks,  
specifying a way to be activated, and the replacement size for the  
10 respective tasks; and

a rewriting unit operable to rewrite said control register so as  
to hold way data and a replacement size corresponding to a task  
being executed.

15 19. The cache memory according to Claim 1, further comprising:  
a storage unit operable to store, for each cache entry, 1-bit  
access information indicating whether or not the cache entry has  
been accessed, the cache entry holding data which is a unit of  
caching; and

20 a selection unit operable to select a cache entry to be replaced  
from among cache entries corresponding to access information  
indicating that a cache entry has not been accessed.

25 20. The cache memory according to Claim 19, further comprising:  
a register operable to hold data indicating a round position for  
selecting, in a round robin, one way from a plurality of ways that can  
be replaced; and

a reset unit operable to reset, when the contents of said  
control register are updated by said updating unit, information  
30 indicating an access order for ways, and the data, in said register,  
indicating the round position.

21. A control method for controlling an N-way set-associative cache memory, comprising:

a step of setting, to a control register, way data indicating one or more ways among N ways; and

5 a control step of activating the way indicated by the control register.

22. The control method according to Claim 21,

10 wherein in said controlling, at least replacement is restricted for a way other than the active way indicated by the control register.

23. The control method according to Claim 22, further comprising an updating step of reading-out, from a holding unit, way

15 data corresponding to a task being executed, and writing the read-out way data into the control register, the holding unit holding way data for respective tasks, the way data specifying a way to be activated.

20

25